The industry standard for reliable USB video capture



AV.io series

The simplest way to capture video. Automatic configuration with no drivers to install.



Epiphan AV.io 4K™

Capture 4K over HDMI in perfect fidelity or use hardware scaling to capture any resolution needed for your application.



4096 × 2160 - 30 fps 1920 × 1080 - 60fps



Epiphan AV.io HD+™

Capture 1080p video from any HDMI camera or device with nearly zero latency, bringing in audio through HDMI, the 3.5 mm input, or both.



1920 × 1080 - 60fps

AV.io series

The simplest way to capture video. Automatic configuration with no drivers to install.



Epiphan AV.io SDI+™

Capture 1080p video from any SDI camera or device with nearly zero latency, bringing in audio through HDMI, the 3.5 mm input, or both.





	AV.io 4K	AV.io HD+	AV.io SDI+
Resolution support	Up to 2160 (4K)	Up to 1080p (Full HD)	Up to 1080p (Full HD)
Interface	USB 3.0 USB 2.0	USB 3.0 USB 2.0	SDI (3G-SDI, HD-SDI, SD-SDI), 3.5 mm analog audio
Inputs	НДМІ	HDMI, 3.5 mm analog audio	SDI (3G-SDI, HD-SDI, SD-SDI), 3.5 mm analog audio
Output frame rate	60 fps 1080p 30 fps 4K	60 fps 1080p	60 fps 1080p
Audio support	НДМІ	HDMI, 3.5 mm analog audio	SDI, 3.5 mm analog audio
Works with third-party encoder software	Yes	Yes	Yes
Driverless (UVC)	Yes	Yes	Yes
Automatic image scaling and audio resampling	Yes	Yes	Yes
USB powered	Yes	Yes	Yes
Compression	Uncompressed video capture	Uncompressed video capture	Uncompressed video capture

Your address and contact information here.

Epiphan, Epiphan Video, Epiphan Systems, its products names and logos are tradenames or trademarks of Epiphan Systems Inc. All other company, interface and product names and logos are trademarks or registered trademarks of their respective owners in certain countries. Product descriptions and specifications regarding the products in this document are subject to change without notice.

 $^{^{\}text{\tiny{TM}}}$ and © 2022 Epiphan Systems Inc. All rights reserved.